



FIG.1

**EK 型 / EK Core**

型号 TYPE	图例 FIG.	尺寸 Dimensions ( mm )						
		A	B	C	D	E	F	G
EK28/19	1	27.9±0.5	10.2±0.2	11.9±0.2	8.5±0.2	20.4min	6.6±0.2	11.3±0.3
EK28/20F	1	27.9±0.5	10.2±0.2	11.9±0.2	8.5±0.2	20.4min	6.6±0.2	11.3±0.25
EK28/34E	1	27.9±0.5	16.9±0.25	11.9±0.3	8.5±0.25	20.4min	12.53±0.25	11.3±0.25
EK28/20A	1	28.0+0.4/-0.5	10.2±0.2	11.9±0.2	8.5±0.2	20.4min	6.6±0.2	11.3±0.3
EK29/23H	1	29.3+0.4/-0.7	11.6±0.2	11.8+0.3/-0.2	8.35+0.25/-0.15	22+0.7/-0.4	8.0±0.2	11.1+0.4/-0.2
EK29/29E	1	29.3±0.4	14.6±0.2	11.9±0.2	8.4±0.2	22+0.7/-0.4	11.0±0.2	11.3±0.2
EK49/52	1	49.0±0.5	25.8±0.25	18.0±0.3	15.5±0.25	34.7min	18.5±0.25	17.4±0.25

C1	Ae	Le	Amin	Ve	AL(±25%)				重量 g / PRS
					TP4	TP4A	TP4W	TPW33	
0.64	78.20	50.12		3919.17	3450	3500	4150	4400	22.23
0.64	78.20	50.12		3919.17	3450	3500	4150	4400	22.31
	88.20	73.90		6519.70	2500	2550			34.00
0.64	78.20	50.17		3923.36	3450	3500	4150	4450	22.46
0.72	79.93	57.23		4574.25	3150	3200	3850	4150	24.66
0.90	78.19	69.99		5472.28	2700	2750	3250	3500	29.00
0.49	237.16	115.96		27501.75	4500	4600			148.00