



**URS 型 / URS Core**

型号 TYPE	图例 FIG.	尺寸 Dimensions ( mm )						
		A	B	C	D	E	F	G
URS13.6/9/8A	1	13.5+0.3/-0.2	4.35±0.15	8+0.2/-0.15	4.5±0.15	6.5min	2.55+0.15/-0.1	2.3+0.1/-0.15
URS17	2	16.7±0.3	5.15±0.2	6.0±0.2	4.0±0.2	10.7±0.3	3.15±0.2	2.0±0.2
URS18	1	18.0±0.5	11.0±0.3	11.0±0.3	7.5±0.2	6.15min	7.5±0.3	4.0±0.2
URS18.5E	2	18.5±0.5	11.4±0.3	10±0.3	7±0.3	7.0min	7.4±0.3	
URS18.8	3	18.8±0.2	14.5±0.2	8.5±0.2	8.55±0.2			4.3±0.2
URS19.8	2	19.85±0.4	11.8±0.2	13.05±0.3	8±0.15	8.85±0.4	8.6±0.2	
URS25A	4	25.25±0.4	11.4±0.2	19.8±0.3	9.5±0.2	12.0min	7.9±0.25	
URS26.2	5	26.2±0.35		20±0.3	10±0.2	10.8min	11.1+0.25/-0	5±0.2

C1	Ae	Le	Amin	Ve	AL(±25%)				重量 g / PRS
					TP4	TP4A	TP4W	TPW33	
2.5	13.4	34		462	750	780	900	980	2.30
3.9	10.9	42.8		468.1	520	550	650	700	2.60
1.5	39.7	59.36		2361.5	1500	1580	1800	1950	10.50
1.6	37.5	61.4		2301	1300	1350	1700	1800	10.50
1.77	42.2	74.9	36.55	3160.7	1200	1250	1500	1650	15.60
1.52	42.96	65.17		2799.7	1520	1580	1800	1900	13.90
1.3	62.5	78.8		4926.8	1900	1960	2400	2500	25.20
0.95	91	86.2		7847	2500	2600	3100	3400	43.10